COURT DIAGRAM Standard English Measurements MIN. 6' SERVING 30' AREA Libero replacement zone 60' Team Bench Attack line 10' Referee's Platform - 3'-CF ➤ RF 10' Officials Sub Attack line Libero replacement zone There shall be a minimum clearance of 6' completely surrounding the court. LB **≺** CB RB Team Bench SERVING AREA I MIN. 8'' 6'

Note: All lines on the court are 2 inches wide. For the center line, a solid or shadow-bordered 2-inch-wide line is permissible. The border or outlines for the shadowed center line shall be at least ¼-inch wide and shall be within the 2-inch width. It is recommended that the court should be clear of obstructions and the overhead playable area should be at least 23 feet high.

COURT DIAGRAM Metric Measurements 2m 15 cm SERVING 9 m ·20 cm AREA Libero replacement zone 18 m Team Bench Attack line 3m Referee's Platform -.91m-CF ➤ RF 3m Sub zone Officials Attack line Libero replacement zone There shall be a minimum clearance of 6' completely surrounding the court. LB **≺** CB RB Team Bench SERVING AREA I 2m 20 cm

Note: All lines on the court are 5 centimeters wide. For the center line, a solid or shadow-bordered 5-centimeters wide line is permissible. The border or outlines for the shadowed center line shall be at least .64 centimeters wide and shall be within the 5-centimeters width. It is recommended that the court should be clear of obstructions and the overhead playable area should be at least 7 meters high.